

Package: ggwizard (via r-universe)

June 26, 2026

Title Create Beautiful ggplot2 Charts Without Coding

Version 0.1.0

Description A point-and-click Shiny application that guides non-programmers through importing CSV or Excel data, previewing it, and generating publication-quality ggplot2 charts. Supports bar, line, scatter, time series, histogram, box, violin, and area plots with full customisation of labels, themes, colours, and font styles. Outputs are saved to a timestamped folder along with a reproducible R script and a run log.

License MIT + file LICENSE

URL <https://github.com/ebenogoe/ggwizard>

BugReports <https://github.com/ebenogoe/ggwizard/issues>

Depends R (>= 4.1.0)

Imports bsicons, bslib (>= 0.5.0), DT, fontawesome, fs, ggplot2, golem (>= 0.5.1), htmlwidgets, plotly, readr, readxl, rlang, shiny (>= 1.7.0), shinybusy, shinyFiles, shinyjs, shinyWidgets, stats, utils

Suggests testthat (>= 3.0.0)

Encoding UTF-8

Language en-US

RoxygenNote 7.3.3

Config/testthat/edition 3

Config/pak/sysreqs cmake make libicu-dev libuv1-dev libssl-dev libx11-dev zlib1g-dev

Repository <https://ebenogoe.r-universe.dev>

Date/Publication 2026-06-26 00:49:08 UTC

RemoteUrl <https://github.com/ebenogoe/ggwizard>

RemoteRef main

RemoteSha de47a0ff534cd6fc5ae878bb9e8493fef022835b

Contents

run_app	2
Index	3

run_app	<i>Run the ggWizard Shiny Application</i>
---------	---

Description

Launches the ggWizard point-and-click chart builder in a browser window.

Usage

```
run_app(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

onStart	A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global.R file can be used for this purpose.
options	Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app.
enableBookmarking	Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app.
uiPattern	A regular expression that will be applied to each GET request to determine whether the ui should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
...	Arguments passed to <code>[golem::get_golem_options()]</code> .

Index

`enableBookmarking()`, [2](#)

`run_app`, [2](#)